

1169 Plastic Hinged Drop Down Loft Access Door

Hinged loft doors with lockable options

Replacement parts available

LOFT - LOC
Loft door operating poles available



Use

- To provide simple, easy access through a ceiling into the loft space

Features and Benefits

- Air permeability measured at 50Pa as 0.00m³ (h.m²) under positive pressure test conditions
- Purpose made product saves time and money compared with traditional joiner-made timber loft access doors
- Independently air leakage tested by BRE
- Excellent aesthetic appearance
- Factory finished and ready to fit straight from the box
- Insulated door panel with integral draught/vapour seal
- Maintenance free, no need to paint
- Hinged design allows use of a telescopic loft ladder
- Acoustic performance of 30dB
- Secure key operated lock option available

Quality

- Satisfies all NHBC requirements
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Complies with Building Reg. document L1A & L2A (2013 Edition)
- Meets all relevant British Standards

Material and Colour Choice

- The door and frame are one piece injection moulded polypropylene
- Insulation is CFC free expanded polystyrene foam
- Door and frame available in white only RAL 9010

Installation Advice

- This product is designed to fit between 38mm thick trussed rafters or ceiling joists spaced at 600mm centres to provide a clear joist opening width of 562mm
- If the roof design does not provide this joist opening width, a suitable opening must be formed
- Trimmers must be installed across the ends of the frame. These must be spaced to give a clear opening length of 662mm
- Frame fixes with ten screws, three through each side and two through each end
- Fit the loft access door after the ceiling has been plaster boarded and skimmed
- The frame must be a good fit into the trimmed opening. Never try to force it into an opening that is too small. If the opening is too large use packers to ensure a good fit

Product Codes

Description	Frame Fitting Size	Clear Opening Size	Insulation U-value	Product Codes
1169 Plastic Hinged Drop Down Loft Access Door	562 x 662mm	526 x 626mm	0.82 W/m ² K	1169
1169 Plastic Hinged Drop Down Loft Access Door with Key Lock	562 x 662mm	526 x 626mm	0.82 W/m ² K	1169KL
1169 Plastic Hinged Drop Down Loft Access Door - 0.35 U-value	562 x 662mm	526 x 626mm	0.35 W/m ² K	1169/35
1169 Plastic Hinged Drop Down Loft Access Door with Key Lock - 0.35 U-value	562 x 662mm	526 x 626mm	0.35 W/m ² K	1169/35KL
1169 Plastic Hinged Drop Down Loft Access Door - 0.25 U-value	562 x 662mm	526 x 626mm	0.25 W/m ² K	1169/25
1169 Plastic Hinged Drop Down Loft Access Door with Key Lock - 0.25 U-value	562 x 662mm	526 x 626mm	0.25 W/m ² K	1169/25KL

Technical Considerations

- Timloc loft access doors comply with Building Regulations; 'THE BUILDING REGULATIONS 'Conservation of fuel and power' APPROVED DOCUMENT L1A & L2A (2013 Edition)
- Timloc loft access doors comply with the most recent Building Regulations; 'THE BUILDING REGULATIONS 2000 'Conservation of fuel and power' APPROVED DOCUMENT L1A & L2A (2006 Edition)
- The Timloc loft access door has demonstrated a zero 0.00m³/(h.m²) air leakage at 'positive' 50Pa to exceed requirements set in the Building Regulation Part L1A & L2A while fully complying with BS5250:2021 the Code of Practice for control of condensation in buildings
- Timloc loft access doors contain polystyrene insulation with a Thermal Conductivity of 0.038W/mK. For this reason a correction U value of 0.004W/m²k should be calculated to the proposed U value figures for a ceiling (U value for a ceiling not to exceed 0.16W/m²k)
- With reference to insulation, the products in this range do not use, contain or produce Urea Formaldehyde, CFC's or indeed any of the so called soft CFC's, ie. HCFC's & HFA's. They have an ozone depletion potential of zero and Global Warming Potential of less than 5

Product Dimensions

