

# AIRBRICK DATASHEET

## Airbrick ventilator available in a range of colours

### Use

- In conjunction with the 1201/1201XL/1201XL+ telescopic underfloor vent for providing ventilation below suspended ground floors.
- In conjunction with cavity sleeves for ventilation through external walls to a building interior.

### Features & Benefits

- Equivalent area of 6170mm<sup>2</sup> per air brick.
- Unique stepped front grille greatly reduces the entry of wind driven rain.
- 6.5mm wide front grille openings comply with BS 5440 Pt 2 and British Gas requirements.
- Integral clip together facility allows multiple airbricks to be stacked to form 9" x 6" and 9" x 9" sizes.
- Available in a range of colours to blend in with various brick types.
- Very tough and robust.
- Durable and totally resistant to decay.

### Quality

- Satisfies all NHBC requirements.
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001.
- Complies with all relevant Building Regulations.
- Meets all relevant British Standards.
- Equivalent area marking to front face of airbrick to comply with BS EN 13141-1 : 2004.

### Material & Colour

- Injection moulded Polypropylene.
- Available in Buff, Terracotta, Grey, Brown, Black, White and Blue Black.



### How to Order

- Airbrick quantity will be relative to the number of telescopic underfloor ventilators or cavity sleeves required.
- State the colour required.

### Environmental Product Declaration

A quantification of environmental information regarding the life cycle of the Airbrick. GWP total is for production stages A1-A3. Verified in accordance with ISO 14025. View the full EPD at [timloc.co.uk](http://timloc.co.uk).

Product	EPD Reference	EPD Mass (KG)	GWP A1-A3 (KG CO2e)
1201ABWH	EPD HUB, HUB-2180	0.118	1.65E-01
1201AB	EPD HUB, HUB-1836	0.1	2.50E-03

### Bill of Quantity

F30 Accessories/sundry items for brick/block/stone walling Clause 160 | AIRBRICK

- To BS493, Class 1, built in as the work proceeds.
- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567, W: [www.timloc.co.uk](http://www.timloc.co.uk)
- Reference: 1201AB
- Design: Rectangular
- Work size: Each unit 69mm coursing x 215mm,
- (Equivalent area 6170mm<sup>2</sup>)
- Material: Thermoplastic
- Colour: (Black, White, Brown, Buff, Grey, Blue Black or Terracotta)
- Optional Accessories: e.g. 1201 Telescopic Under Floor Vent (6,500mm<sup>2</sup> with Airbrick)

### Installation Advice

- Always use in conjunction with a Timloc telescopic underfloor ventilator, or cavity sleeve, depending on the application

## Product Codes

Description	Height	Width	Length	Colour	Equivalent Area	Pack Quantity	Lead Time	Product Codes
Airbrick	69mm	60mm	215mm	Blue Black	6170mm <sup>2</sup>	20	Next Working Day	1201ABBB
Airbrick	69mm	60mm	215mm	Black	6170mm <sup>2</sup>	20	Next Working Day	1201ABBL
Airbrick	69mm	60mm	215mm	Brown	6170mm <sup>2</sup>	20	Next Working Day	1201ABBR
Airbrick	69mm	60mm	215mm	Buff	6170mm <sup>2</sup>	20	Next Working Day	1201ABBU
Airbrick	69mm	60mm	215mm	Grey	6170mm <sup>2</sup>	20	Next Working Day	1201ABGR
Airbrick	69mm	60mm	215mm	Terracotta	6170mm <sup>2</sup>	20	Next Working Day	1201ABTE
Airbrick	69mm	60mm	215mm	White	6170mm <sup>2</sup>	20	Next Working Day	1201ABWH