

ROOFLINE

by **timloc**

Tile Ventilators

Ventilators to suit most common styles of roof tiles



TV8



TV62FRA
Sepia



TV62MEN
Terracotta



TV62MLM
Red



TV62MDA
Anthracite

Use

- To provide inconspicuous ventilation to suit most types of roof tiles
- Suitable for high or low level venting
- Can be used for mechanical extraction or with soil pipes

Features and Benefits

- High performance while retaining the aesthetics of roof design
- Suitable for use with a wide range of roof tile profiles
- Range of standard colours and profiles
- UV stable for continuous exposure
- Quick to install, requiring no special tools or maintenance

Quality

- Satisfies all NHBC requirements
- Meets requirements of Building Regulations Approved Document Part F1, Part F2 and BS 5250:2011 'Code of practice for control of condensation in buildings'

Material and colour choice

- TV8 in PVC-u
- TV62 in polypropylene
- Available in terracotta, red, sepia and anthracite

Products in the System

TV8 plain tile ventilator

- For small, non-interlocking clay and concrete plain tiles. It is suitable for high/low level venting in roofs with minimum pitches of 35° (clay tiles) and 40° (concrete tiles). Each vent has a slotted inhibitor to keep out large insects and vermin and requires a minimum of batten and tile trimming during installation. Free vent area 7500mm².

TV62 profiled tile ventilator

- Profiles to suit most common styles of interlocking roof tiles.
- Suitable for high or low level venting in roofs with pitches of 22.5° and over and can be used to supplement or replace other ventilation such as dry ridge, abutment or eaves systems. Also suitable for ventilation of compartmental roof spaces, such as fire walls. Free vent area 10,000 mm².

Installation Advice

- For TV8 a 'V' cut is made immediately below the batten. The "pennant" is pulled up tightly round the batten and pinned in place
- For TV62 at each ventilating tile position the underlay must be cut to form the required opening and its edge folded, and where necessary, supported to prevent the ingress of water. The vents are then laid and fixed by the roofer in place of an ordinary tile

How to Order

- Determine the quantity required according to the use for which the ventilator is being put, specify the type of tile being used and the colour.

Bill of Quantity

G20 Carpentry/Timber Framing/First Fixing

Clause

900^A EAVES SOFFIT VENTILATION

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: www.timloc.co.uk
- Product Reference: TV8/TV62 MEN etc
- Type: Plain Tile Ventilator/Profiled Tile Ventilator
- To suit Tile: Plain Tile/Profiled Tile Marley etc
- Colour: Terracotta/Red/Sepia/Anthracite

Product Codes

Available in Terracotta, red, sepia and anthracite

Description	Suitable for	Product Code
Inline plain tile vent		TV8*
Plain tile venti adaptor		TV8AD
Inline profiled tile vent	Marley Mendip Redland Grovebury and similar profiles	TV62MEN*
Inline profiled tile vent	Marley Modern Russell Grampian Redland Mini Stoneworld and similar profiles	TV62MDA*
Inline profiled tile vent	Marley Ludlow and similar profiles	TV62MLM*
Inline profiled tile vent	Marley Double Roman Russell Double Roman Redland Landmark Double Roman Sandtoft Double Roman and similar profiles	TV62FRA*
Profiled tile vent adaptor		TV62AD

* Include colour choice option (TE=Terracotta, RE=Red, SE=Sepia, AN=Anthracite)