

EAVES BIRD COMB FILLER DATASHEET

Designed to prevent entry of birds and vermin below profiled roof tiles

Use

- At the eaves of a roof.
- Below profiled roof tiles to exclude birds and vermin.

Features & Benefits

- Effective, quick and easy to fit.
- Durable and totally resistant to decay.
- Supplied in convenient 1m lengths.

Quality

- Satisfies all NHBC requirements.
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001.
- Complies with all relevant Building Regulations.
- Meets all relevant British Standards.

Material & Colour

- Injection moulded in polypropylene.
- Available in black only.

How to Order

- Measure the overall length of the eaves and divide by 1m to determine the number of combs required.

Bill of Quantity

G20 Carpentry/Timber Framing/First Fixing

Clause 900⁺ | EAVES SOFFIT VENTILATION

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: www.timloc.co.uk
- Product Reference: 1136
- Type: Eaves Comb Filler (1000mm)
- Colour: Black

Product Codes

Description	Depth of Comb	Length	Colour	Pack Quantity	Lead Time	Product Codes
Eaves bird comb filler	55mm	1m	Black	50	Next Working Day	1136




Environmental Product Declaration

A quantification of environmental information regarding the life cycle of the Eaves Bird Comb Filler. GWP-fossil total is for production stages A1-A3. Verified in accordance with ISO 14025. View the full EPD at timloc.co.uk.

EPD Reference	EPD Mass (KG)	GWP-fossil, A1-A3 (kgCO ₂ e)
HUB-1836	0.074	3.241E-02

Product Dimensions



Installation Advice

- Fit on the top of the fascia board before tiles are laid. The comb must angle outwards away from the roof
- Secure with clout nails through the holes provided
- Bed bottom row of tiles on to the comb