

# PUSH-IN SOFFIT VENT

# DATASHEET

**Efficient, circular ventilator in a range of colours**

## Use

- For roof eaves ventilation.
- For remedial work on existing roofs.
- On roofs requiring ventilation equivalent to a 10mm continuous opening.
- On roofs where the eaves incorporate a soffit board.

## Features & Benefits

- Efficient, unobtrusive and easy to fit.
- Can be fitted to existing soffit boards in situ.
- 4mm wide holes comply with BS 5250 : 2021.
- Durable and totally resistant to decay.
- UV stabilised and colourfast.

## Quality

- Satisfies all NHBC requirements.
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001.
- Complies with all relevant Building Regulations.
- Meets all relevant British Standards.

## Material & Colour

- Manufactured by injection moulding in polypropylene.
- Available in grey, white, black or brown.

## Products in the System

### Push in vents - 1139/1140/1141/1142

- All provide a free airflow of 2000mm<sup>2</sup> per unit and should be spaced at 200mm centres to achieve ventilation equivalent to a continuous 10mm opening.

## How to Order

- Specify which colour is preferred.
- Measure the overall length of the eaves to be ventilated and divide by 200mm to determine the number of ventilators required.



1139



1140



1141



1142



## Bill of Quantity

### G20 Carpentry/Timber Framing/First Fixing

Clause 910<sup>^</sup> | EAVES SOFFIT VENTILATION


- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: [www.timloc.co.uk](http://www.timloc.co.uk)
- Product Reference: 1139/1140/1141/1142
- Type: Push in Soffit Vent (70mm diameter)
- Colour: (Black, White, Brown, Grey)
- Airway: Provide the equivalent of a continuous opening of not less than 10mm for the full length of eaves.

## Environmental Product Declaration

A quantification of environmental information regarding the life cycle of the Push-In Soffit Vent. GWP total is for production stages A1-A3. Verified in accordance with ISO 14025. View the full EPD at [timloc.co.uk](http://timloc.co.uk).

Product	EPD Reference	EPD Mass (KG)	GWP A1-A3 (KG CO <sub>2</sub> e)
1139, 1141 & 1142	EPD HUB, HUB-1836	0.0121	3.03E-04
1140	EPD HUB, HUB-2180	0.0124	1.74E-02

## Product Dimensions



## Installation Advice

- Use to ventilate pitched roofs, where the pitch of the roof is 15 degrees or more, and the roof void is attic or loft space
- Do not use to ventilate pitched roofs where the pitch of the roof is less than 15 degrees, flat roofs or any roof where living accommodation is contained within the roof space
- Space ventilators at 200mm centres
- Take care to ensure the fixing holes are cut accurately with a diameter of between 69-70mm. If the holes are oversize, the ventilators will not fix securely
- The ventilators should be a firm push fit into the fixing holes
- Ventilation must be provided for the full length of the eaves and along both sides of the building to create a cross flow ventilation action
- Please see technical section for more details.

## Product Codes

Description	Colour	Pack Quantity	Lead Time	Product Codes
Push-In Soffit Vent	Grey	10	Next Working Day	1139
Push-In Soffit Vent	White	10	Next Working Day	1140
Push-In Soffit Vent	Black	10	Next Working Day	1141
Push-In Soffit Vent	Brown	10	Next Working Day	1142