

# FRSTOP

## Fire-Rated Cavity Stop Sock

Fire-rated thermal and acoustic cavity stop sock

### Use

- To restrict the spread of flames within external masonry
- To further minimise the effect of flanking noise pollution at wall junctions

### Features and Benefits

- FRstop cavity stop socks are lengths of low resin, non-combustible, rockfibre mineral wool sleeved in 35 micron polythene for on-site weather protection
- 1 hour fire integrity and minimum 15 minute insulation
- Available in standard widths of 50, 75, 85, 90, 100, 115, 125 and 150mm
- Also available to suit cavity widths of up to 300mm
- Special cavity widths are available on request up to 300mm

### Quality

- Satisfies all NHBC requirements
- Complies with Building Regulations Approved Document B
- Meets all relevant British Standards
- Independently tested by Warrington Fire
- Meets the requirements of the Robust Details

### Material and Colour Choice

- Manufactured using Rockfibre mineral wool
- Rockfibre uses no CFC's, HCFC's in the manufacturing process
- Thermal conductivity of Rockfibre insulation 0.037w/mK
- Bag colour according to size range:

Product Code	Bag Colour
FRSTOP50	Yellow <span style="color: yellow;">●</span>
FRSTOP65 - 100	Blue <span style="color: blue;">●</span>
FRSTOP115 - 140	Green <span style="color: green;">●</span>
FRSTOP150 - 200	Red <span style="color: red;">●</span>
FRSTOP210 - 300	Blue <span style="color: blue;">●</span>

### Installation Advice


- FRstop is designed to friction fit within the cavity and is easily installed both vertically and horizontally into the cavity during construction. Care should be taken to ensure butt joints are closely fitted and the cavity sock fully fills the cavity.
- This method should be incorporated with a preformed horizontal cavity tray (refer to Technical Department for appropriate type) and proprietary wall weep vents (1143) at 900mm centres to prevent water ingress from bridging the cavity.

### Product Codes

Product Code	To Suit Cavity Width	Bag Colour	Dimensions	Pack Quantity	Lead Time
FRSTOP50	50mm	Yellow	65 x 65 x 1200mm	20	Next working day
FRSTOP75	75mm	Blue	85 x 85 x 1200mm	18	Next working day
FRSTOP85	85mm	Blue	100 x 85 x 1200mm	1	Next working day
FRSTOP90	90mm	Blue	100 x 85 x 1200mm	1	Next working day
FRSTOP100	100mm	Blue	110 x 100 x 1200mm	1	Next working day
FRSTOP115	115mm	Green	130 x 100 x 1200mm	1	Next working day
FRSTOP125	125mm	Green	140 x 100 x 1200mm	1	Next working day
FRSTOP150	150mm	Red	160 x 120 x 1200mm	1	Next working day

**NB. Non standard cavity sizes up to 300mm are available to special order**

Available in individual lengths



Also available to suit cavity widths of up to 300mm



### How to Order

- To calculate quantities divide the overall length of the required cavity wall run by 1.2m, allow an additional unit for each corner for cutting. Always round up to the next whole number
- Determine and stipulate the cavity width that FRstop needs to suit

### Bill of Quantity

F30 Accessories/sundry items for brick/block/stone walling  
Clause

370 PREFORMED CAVITY TRAY / ACCESSORIES

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorks. DN14 7SD. T: 01405 765 567 W: www.timloc.co.uk
- Types(s) and location(s): FRstop - thermal and acoustic fire stops to be installed vertically and horizontally as work proceeds. Position where a party wall meets the cavity wall or at floor levels, supplied in 1.2m lengths and butt jointed.
- Reference: FRstop