

RADON SUMP

# DATASHEET

**Prefabricated plastic sump for use where sub floor depressurisation is required**

### Use

- Where sub floor depressurisation is required under full radon protection.
- The sump is installed beneath the floor slab in non suspended floor applications and vented to atmosphere via a connecting 110mm drainage pipe to an external source and capped off with proprietary products i.e. air bricks & telescopic under floor vents or roof vents.

### Features & Benefits

- Compatible with 110mm drainage pipes.
- Single piece moulding eliminates the need for on-site fabrication preventing errors through poor workmanship.
- Easy to handle and position.
- Tough, durable and puncture resistant.
- Spigot ends can be cut along the indented lines as required to provide extra pipe connections.
- Two or more sumps can be connected with pipework to provide more capacity for larger or more complex groundwork sites with multiple compartments.

### Quality

- Satisfies all NHBC requirements.
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001.
- Complies with all relevant Building Regulations.
- Meets all relevant British Standards.
- UK Design Registration Number 6185786.

### Product Codes

Description	Colour	Pack Quantity	Lead Time	Product Codes
Radon Sump	Black	1	Next Working Day	RSUMP01



### Material & Colour

- Moulded in 3mm thick medium density polyethylene.
- Available in black only.

### Product Dimensions

