



ROOFLINE

by **timloc**

6m Roll Out Dry Fix Clay Ridge Kit

Convenient mechanical fix solution for clay roof ridge installations.

Use

- Most types of clay roof tiles
- Round or angled ridge tiles
- Most pitched roof types from 15-55°
- New build and retro-fit projects

Features and Benefits

- Preassembled fixing screws and clamping plates
- Ridge union with adjustable clip positions to suit a range of clay ridge tile thicknesses (30mm max)
- Universal ridge batten strap for ease and flexibility
- Long lasting, reliable and virtually maintenance free
- Protects against wind uplift, water ingress and general deterioration
- Provides 5000mm²/m (5mm continuous) ridge ventilation
- Easy, fast, clean and generally safer mortar free installation
- Water resistant yet air permeable membrane roll
- Strong, malleable and corrosion resistant aluminium flashing secured to roll
- 55mm wide ridge union width provides additional water bar protection
- Assurance of stainless steel clamping plates
- Maintains consistently smart appearance
- Not impacted by building settlement
- Helps prevent entry of large insects, birds and vermin into the roofline

Quality

- Helping to meet:
 - BS 5534 Code of practice for slating and tiling
 - BS 5250 Code of practice for control of condensation in buildings
- Complies with all other relevant regulations and standards
- Independently tested and complies with BS 8612

Material and Colour Choice

- Ridge unions and clips manufactured from UV protected and colour fast polypropylene
- Water resistant and ventilated roll membrane with attached self-adhesive and coloured aluminium flashing (colour may vary from pictured)
- Galvanised steel ridge batten straps
- Stainless steel screws and clamping plates
- Available in black only
- All kits are supplied with black ridge unions and clips

Installation Advice

- Please refer to www.timloc.co.uk for recommended installation guidance.



Components Supplied in the Pack

- 1 x 6m vent roll membrane with self-adhesive flashing
- 20 x fixing screws and clamping plates
- 20 x ridge unions
- 40 x ridge union clips
- 10 x ridge batten straps

How to Order

- Order 1 pack for roof ridge lengths up to 6m
- Order further kits to cover lengths over 6m. These can be installed sequentially
- Please allow for a minimum roll membrane overlap of at least 150mm

Product Codes

Depth of Comb	Colour	Product Code
6m roll out dry fix clay ridge kit	Black	54713
20x ridge unions & 40x ridge clips	Black	54715
20x fixing screws & clamping plates	Silver	54716

Product Dimensions

