

THERMO-LOC

# CAVITY CLOSERS & STOP SOCKS

**Fire rated & non-fire rated** cavity closers & stop socks

**timloc**  
building products

# CAVITY CLOSERS & STOP SOCKS


Use the table below to establish which cavity closer is best suited to your project specification. Alternatively, get in touch with our Technical department who will be happy to assist with your enquiry:

	Thermo-Loc Platinum Multi	Thermo-Loc Platinum +	Thermo-Loc Platinum + FX	Thermo-Loc FR30	Thermo-Loc FR60	Thermo-Loc FR60+
Product Code	CC2.4PPS/...	PP2.4/...	FX2.4/...	CC2.4FR/...	FR60/...	FR60/...
Shape	T	C	C FX	C FX	C FX	C FX
Fire Rated	✗	✗	✗	✓	✓	✓
Check Reveal	✗	✓	✓	✓	✓	✓
Profile	50 - 100 single 100 - 150 single	50 - 100 single 105 - 150 double	50 - 100 single 105 - 150 double	50 - 100 single 105 - 300 double	50 - 100 single 105 - 150 single	150 - 300 single
Length	2.4m	2.4m	2.4m	2.4m	2.4m	2.4m
Thickness	20mm	25mm	25mm	25mm	30mm	50mm
Multi Option	✓ up to 150mm	✓ up to 100mm	✓ up to 100mm	✗	✗	✗
Building Reg. Parts C+L Compliant	✓	✓	✓	✓	✓	✓
Building Reg. Part B Compliant	✗	✗	✗	✓	✓	✓

We recommend customers take advantage of our technical advisory service. Our technical team will be pleased to advise on the most suitable products for the application and can prepare a fully itemised schedule of quantities if required.

The THERMO-LOC range is designed to lock warmth inside a building. Thermo-loc offers greater protection against the risk of condensation, at a lower material thickness, when compared to standard cavity closers.


**THERMO-LOC**  
Platinum Multi



Single Profile 50 - 100mm




**THERMO-LOC**  
Platinum+



Single Profile 100 - 150mm



**THERMO-LOC**  
Platinum+ FX




Single Profile 50 - 100mm



Double Profile 105 - 150mm



**THERMO-LOC**  
FR30




Single Profile 50 - 100mm



Double Profile 105 - 150mm



**THERMO-LOC**  
FR60




Single Profile 50 - 100mm



Double Profile 105 - 300mm



**THERMO-LOC**  
FR60+



Single Profile 50mm - 100mm




Single Profile 105mm - 150mm



Single Profile 150mm - 300mm



## PLATINUM MULTI CAVITY CLOSER



**Thermo-loc Platinum Multi  
50-100mm**



**Thermo-loc Platinum Multi  
100-150mm**

### USE

- To close the cavity at external doors, window jambs and sills
- To provide thermal insulation and prevent 'cold bridging'
- To provide a DPC at external doors, window jambs or sills
- Suitable for cavities up to 150mm


All available  
in **2.4m**  
lengths

Cavity closers designed to eliminate damp and cold bridging around doors, windows, and sills.


Suitable for a range of cavity sizes up to 150mm by easily cutting to size using the pre-cut grooves. 20mm insulation thickness. Compliant with Building Regulation Approved Documents C, L1 and L2 and satisfies BRE document 'Thermal Insulation: avoiding risks'.

Product Code	Description	Cavity Width	Pack Qty	Lead Time
CC2.4PPS/MULTI100	Thermo-loc Platinum Multi 50-100mm	50-100mm	10	Next Working Day
CC2.4PPS/MULTI150	Thermo-loc Platinum Multi 100-150mm	100-150mm	10	Next Working Day


## PLATINUM + CAVITY CLOSER



Thermo-loc Platinum +  
Single Profile



Thermo-loc Platinum +  
Double Profile



Thermo-loc Platinum +  
CR Multi

### USE

- To close the cavity at external doors, window jambs and sills
- To provide thermal insulation and prevent 'cold bridging'
- To provide a DPC at external doors, window jambs or sills
- Suitable for cavities up to 150mm


All available  
in **2.4m**  
lengths

Cavity closers designed to eliminate damp and cold bridging around doors, windows, and sills.

Single profile for 50mm-100mm cavities, double profile for 105mm-150mm cavities, Multi and Check Reveal Multi options also available. 25mm insulation thickness. Compliant with Building Regulation Approved Documents C, L1 and L2 and satisfies BRE document 'Thermal Insulation: avoiding risks'.

Product Code	Description	Cavity Width	Pack Qty	Lead Time
PP2.4/50	Thermo-loc Platinum +	50mm	10	Next Working Day
PP2.4/75	Thermo-loc Platinum +	75mm	10	Next Working Day
PP2.4/90	Thermo-loc Platinum +	90mm	10	Next Working Day
PP2.4/100	Thermo-loc Platinum +	100mm	10	Next Working Day
PP2.4/100MULTI	Thermo-loc Platinum + Multi	50-100mm	10	Next Working Day
PP2.4/120	Thermo-loc Platinum +	120mm	10	Next Working Day
PP2.4/125	Thermo-loc Platinum +	125mm	10	Next Working Day
PP2.4/130	Thermo-loc Platinum +	130mm	10	Next Working Day
PP2.4/150	Thermo-loc Platinum +	150mm	10	Next Working Day
PP2.4/CR100MULTI	Thermo-loc Platinum + CR Multi	50-100mm	10	3 Working Days


## PLATINUM + FX CAVITY CLOSER



**Thermo-loc Platinum + FX  
Single Profile**



**Thermo-loc Platinum + FX  
Double Profile**



**Thermo-loc Platinum + FX  
CR Multi**

### USE

- To close the cavity at external doors, window jambs and sills
- To provide thermal insulation and prevent 'cold bridging'
- To provide a DPC at external doors, window jambs or sills
- Suitable for cavities up to 150mm


All available  
in **2.4m**  
lengths

Single profile for 50mm-100mm cavities and double profile for 105mm-150mm cavities. Multi and Check Reveal options also available. 25mm insulation thickness. Compliant with Building Regulation Approved Documents C, L1 and L2 and satisfies BRE document 'Thermal Insulation: avoiding risks'.


Product Code	Description	Cavity Width	Pack Qty	Lead Time
FX2.4/50	Thermo-loc Platinum + FX	50mm	10	Next Working Day
FX2.4/75	Thermo-loc Platinum + FX	75mm	10	Next Working Day
FX2.4/90	Thermo-loc Platinum + FX	90mm	10	Next Working Day
FX2.4/100	Thermo-loc Platinum + FX	100mm	10	Next Working Day
FX2.4/120	Thermo-loc Platinum + FX	120mm	10	Next Working Day
FX2.4/125	Thermo-loc Platinum + FX	125mm	10	Next Working Day
FX2.4/130	Thermo-loc Platinum + FX	130mm	10	Next Working Day
FX2.4/150	Thermo-loc Platinum + FX	150mm	10	Next Working Day
FX2.4/100MULTI	Thermo-loc Platinum + FX Multi	50-100mm	10	Next Working Day
FX2.4/CR50	Thermo-loc Platinum + FX CR	50mm	10	3 Working Days
FX2.4/CR100	Thermo-loc Platinum + FX CR	100mm	10	3 Working Days
FX2.4/CR125	Thermo-loc Platinum + FX CR	125mm	10	3 Working Days
FX2.4/CR150	Thermo-loc Platinum + FX CR	150mm	10	3 Working Days
FX2.4/CR100MULTI	Thermo-loc Platinum + FX CR Multi	50-100mm	10	3 Working Days
CCFIX	Fixing ties	-	100	Next Working Day

# THERMO-LOC FR30

## 30-MINUTE FIRE RATED CAVITY CLOSER



**Thermo-loc FR30  
Single Profile**



**Thermo-loc FR30  
Double Profile**

### USE

- To close the cavity at external doors, window jambs and sills
- To provide thermal insulation and prevent 'cold bridging'
- To provide a DPC at external doors, window jambs or sills
- 30-minutes fire rating and minimum 15 minutes insulation
- Suitable for cavities up to 300mm
- Suitable for timber and masonry walls

All available  
in **2.4m**  
lengths

Independently tested by Warringtonfire to achieve 30-minute fire rating and min. 15 minutes insulation.

Available in single profile for 50mm-100mm cavities and double profile for 105mm-300mm cavities. Cavity barriers for fully rebated and check reveal are also available. 25mm insulation thickness. Compliant with Building Regulation Approved Documents C, B, L1 and L2 and satisfies BRE document 'Thermal Insulation: avoiding risks'.


Product Code	Description	Cavity Width	Pack Qty	Lead Time
CC2.4FR/50	Thermo-loc FR30	50mm	10	Next Working Day
CC2.4FR/65	Thermo-loc FR30	65mm	10	Next Working Day
CC2.4FR/75	Thermo-loc FR30	75mm	10	Next Working Day
CC2.4FR/90	Thermo-loc FR30	90mm	10	Next Working Day
CC2.4FR/100	Thermo-loc FR30	100mm	5	Next Working Day
CC2.4FR/125	Thermo-loc FR30	125mm	5	Next Working Day
CC2.4FR/150	Thermo-loc FR30	150mm	3	Next Working Day
CCFIX	Fixing ties	-	100	Next Working Day

### **NB. Non standard cavity sizes up to 300mm are available to special order. Lead times:**


- Orders for non standard and special sizes upto 50 pieces received before 12pm - Next working day.
- Orders received after 12pm will be despatched the following working day.
- Orders for non standard and specials sizes over 50 pieces - 3 working days.

# THERMO-LOC FR60

## 60-MINUTE FIRE RATED CAVITY CLOSER



**Thermo-loc FR60  
100mm Profile**



**Thermo-loc FR60  
100mm Profile**

### USE

- To close the cavity at external doors, window jambs and sills
- To provide thermal insulation and prevent 'cold bridging'
- To provide a DPC at external doors, window jambs or sills
- 60-minutes fire rating and minimum 15 minutes insulation
- Suitable for cavities up to 150mm
- Suitable for timber and masonry walls

All available  
in **2.4m**  
lengths

Independently tested by Warringtonfire to achieve 60-minute fire rating and min. 15 minutes insulation.

Single profile for 50mm-150mm cavities. 30mm insulation thickness. Compliant with Building Regulation Approved Documents C, B, L1 and L2 and satisfies BRE document 'Thermal Insulation: avoiding risks'.


Product Code	Description	Cavity Width	Pack Qty	Lead Time
FR60/50	Thermo-loc FR60	50mm	5	Next Working Day
FR60/100	Thermo-loc FR60	100mm	5	Next Working Day
FR60/125	Thermo-loc FR60	125mm	5	Next Working Day
FR60/150	Thermo-loc FR60	150mm	5	Next Working Day
FR60/CR50	Thermo-loc FR60 CR	50mm	5	3 Working Days
FR60/CR65	Thermo-loc FR60 CR	65mm	5	3 Working Days
FR60/CR75	Thermo-loc FR60 CR	75mm	5	3 Working Days
FR60/CR90	Thermo-loc FR60 CR	90mm	5	3 Working Days
FR60/CR100	Thermo-loc FR60 CR	100mm	5	3 Working Days
FR60/CR125	Thermo-loc FR60 CR	125mm	5	3 Working Days
FR60/CR150	Thermo-loc FR60 CR	150mm	5	3 Working Days
CCFIX	Fixing ties	-	100	Next Working Day

**NB. Non standard cavity sizes up to 300mm are available to special order. Lead times:**


- Orders for non standard and special sizes upto 50 pieces received before 12pm - Next working day.
- Orders received after 12pm will be despatched the following working day.
- Orders for non standard and specials sizes over 50 pieces - 3 working days.

# THERMO-LOC FR60+

## 60-MINUTE FIRE RATED CAVITY CLOSER



**Thermo-loc FR60+ Profile**



**Thermo-loc FR60+ Profile & Fixing Flange**

### USE

- To close the cavity at external doors, window jambs and sills
- To provide thermal insulation and prevent 'cold bridging'
- To provide a DPC at external doors, window jambs or sills
- 60-minutes fire rating and minimum 15 minutes insulation
- Suitable for cavities above 150mm up to 300mm
- Suitable for timber and masonry walls

All available  
in **2.4m**  
lengths

Independently tested by Warringtonfire to achieve 60-minute fire rating and min. 15 minutes insulation.

Suitable for cavities over 150mm up to 300mm. 50mm insulation thickness. Compliant with Building Regulation Approved Documents C, B, L1 and L2 and satisfies BRE document 'Thermal Insulation: avoiding risks'.


Product Code	Description	Cavity Width	Pack Qty	Lead Time
FR60/175	Thermo-loc FR60+	175mm	2	Variable (see below)
FR60/200	Thermo-loc FR60+	200mm	2	Variable (see below)
FR60/225	Thermo-loc FR60+	225mm	2	Variable (see below)
FR60/250	Thermo-loc FR60+	250mm	2	Variable (see below)
FR60/275	Thermo-loc FR60+	275mm	2	Variable (see below)
FR60/300	Thermo-loc FR60+	300mm	2	Variable (see below)
3322*	Fixing Flange	-	4	Next Working Day
CCFIX	Fixing Ties	-	100	Next Working Day

**\*1 pack supplied per length of Thermo-loc FR60 + cavity closer profile**


**NB. Non standard cavity sizes up to 300mm are available to special order. Lead times:**

- Orders for FR60+ upto 50 pieces received before 12pm - Next working day.
- Orders received after 12pm will be despatched the following working day.
- Orders for FR60+ sizes over 50 pieces - 3 working days.

## 60-MINUTE FIRE RATED CAVITY STOP SOCK FOR MASONRY



**Thermo-loc FR60  
100mm Profile**



**Thermo-loc FR60  
100mm Profile**

### USE

- To restrict the spread of flames within external masonry
- To further minimise the effect of flanking noise pollution at wall junctions

All available  
in **1.2m**  
lengths

Independently tested by Warringtonfire to achieve 60-minute fire rating and min. 15 minutes insulation.

Available to suit cavity widths of up to 300mm. Compliant with Building Regulation Approved Document B, Robust Details and NHBC Standards.

Product Code	To Suit Cavity Width	Dimensions	Fire Integrity	Lead Time
FRSTOP50	50mm	65 x 65 x 1200mm	1 hour	Next Working Day
FRSTOP75	75mm	85 x 85 x 1200mm	1 hour	Next Working Day
FRSTOP85	85mm	100 x 85 x 1200mm	1 hour	Next Working Day
FRSTOP90	90mm	100 x 85 x 1200mm	1 hour	Next Working Day
FRSTOP100	100mm	110 x 100 x 1200mm	1 hour	Next Working Day
FRSTOP115	115mm	130 x 100 x 1200mm	1 hour	Next Working Day
FRSTOP125	125mm	140 x 100 x 1200mm	1 hour	Next Working Day
FRSTOP150	150mm	160 x 120 x 1200mm	1 hour	Next Working Day

**NB. Non standard cavity sizes up to 300mm are available to special order.**

## Product Codes For the entire Timloc range of cavity closers and stop socks.

Product Code	Description	Qty.	Lead Time	Page
CC2.4PPS/MULTI100	Thermo-Loc Platinum Multi Cavity Closer 50-100mm Cav 2.4m	10	Next Working Day	6
CC2.4PPS/MULTI150	Thermo-Loc Platinum Multi Cavity Closer 100-150mm Cav 2.4m	10	Next Working Day	6
PP2.4/50	Thermo-Loc Platinum+ Cavity Closer 50mm Cav 2.4m	10	Next Working Day	7
PP2.4/75	Thermo-Loc Platinum+ Cavity Closer 75mm Cav 2.4m	10	Next Working Day	7
PP2.4/90	Thermo-Loc Platinum+ Cavity Closer 90mm Cav 2.4m	10	Next Working Day	7
PP2.4/100	Thermo-Loc Platinum+ Cavity Closer 100mm Cav 2.4m	10	Next Working Day	7
PP2.4/100MULTI	Thermo-Loc Platinum+ Multi Cavity Closer 50-100mm Cav 2.4m	10	Next Working Day	7
PP2.4/120	Thermo-Loc Platinum+ Cavity Closer 120mm Cav 2.4m	10	Next Working Day	7
PP2.4/125	Thermo-Loc Platinum+ Cavity Closer 125mm Cav 2.4m	10	Next Working Day	7
PP2.4/130	Thermo-Loc Platinum+ Cavity Closer 130mm Cav 2.4m	10	Next Working Day	7
PP2.4/150	Thermo-Loc Platinum+ Cavity Closer 150mm Cav 2.4m	10	Next Working Day	7
PP2.4/CR100MULTI	Thermo-Loc Platinum+ CR Multi Cavity Closer 50-100mm Cav 2.4m	10	3 Working Days	7
FX2.4/50	Thermo-Loc Platinum+ FX Cavity Closer 50mm Cav 2.4m	10	Next Working Day	8
FX2.4/75	Thermo-Loc Platinum+ FX Cavity Closer 75mm Cav 2.4m	10	Next Working Day	8
FX2.4/90	Thermo-Loc Platinum+ FX Cavity Closer 90mm Cav 2.4m	10	Next Working Day	8
FX2.4/100	Thermo-Loc Platinum+ FX Cavity Closer 100mm Cav 2.4m	10	Next Working Day	8
FX2.4/100MULTI	Thermo-Loc Platinum+ FX Multi Cavity Closer 50-100mm Cav 2.4m	10	Next Working Day	8
FX2.4/120	Thermo-Loc Platinum+ FX Cavity Closer 120mm Cav 2.4m	10	Next Working Day	8
FX2.4/125	Thermo-Loc Platinum+ FX Cavity Closer 125mm Cav 2.4m	10	Next Working Day	8
FX2.4/130	Thermo-Loc Platinum+ FX Cavity Closer 130mm Cav 2.4m	10	Next Working Day	8
FX2.4/150	Thermo-Loc Platinum+ FX Cavity Closer 150mm Cav 2.4m	10	Next Working Day	8
FX2.4/CR50	Thermo-Loc Platinum+ FX Cavity Closer CR 50mm Cav 2.4m	10	3 Working Days	8
FX2.4/CR100	Thermo-Loc Platinum+ FX Cavity Closer CR 100mm Cav 2.4m	10	3 Working Days	8
FX2.4/CR100MULTI	Thermo-Loc Platinum+ FX Multi Cavity Closer CR 50-100mm Cav 2.4m	10	3 Working Days	8
FX2.4/CR125	Thermo-Loc Platinum+ FX Cavity Closer CR 125mm Cav 2.4m	10	3 Working Days	8
FX2.4/CR150	Thermo-Loc Platinum+ FX Cavity Closer CR 150mm Cav 2.4m	10	3 Working Days	8
CC2.4FR/50	Thermo-Loc FR30 Cavity Closer 50mm Cav 2.4m	10	Next Working Day	9
CC2.4FR/65	Thermo-Loc FR30 Cavity Closer 65mm Cav 2.4m	10	Next Working Day	9
CC2.4FR/75	Thermo-Loc FR30 Cavity Closer 75mm Cav 2.4m	10	Next Working Day	9
CC2.4FR/90	Thermo-Loc FR30 Cavity Closer 90mm Cav 2.4m	10	Next Working Day	9
CC2.4FR/100	Thermo-Loc FR30 Cavity Closer 100mm Cav 2.4m	5	Next Working Day	9
CC2.4FR/125	Thermo-Loc FR30 Cavity Closer 125mm Cav 2.4m	5	Next Working Day	9
CC2.4FR/150	Thermo-Loc FR30 Cavity Closer 150mm Cav 2.4m	3	Next Working Day	9
FR60/50	Thermo-Loc FR60 Cavity Closer 50mm Cav x 2.4m	5	Next Working Day	10
FR60/100	Thermo-Loc FR60 Cavity Closer 100mm Cav x 2.4m	5	Next Working Day	10
FR60/125	Thermo-Loc FR60 Cavity Closer 125mm Cav x 2.4m	5	Next Working Day	10
FR60/150	Thermo-Loc FR60 Cavity Closer 150mm Cav x 2.4m	5	Next Working Day	10
FR60/CR50	Thermo-Loc FR60 Cavity Closer CR 50mm Cav x 2.4m	5	3 Working Days	10
FR60/CR65	Thermo-Loc FR60 Cavity Closer CR 65mm Cav x 2.4m	5	3 Working Days	10
FR60/CR75	Thermo-Loc FR60 Cavity Closer CR 75mm Cav x 2.4m	5	3 Working Days	10
FR60/CR90	Thermo-Loc FR60 Cavity Closer CR 90mm Cav x 2.4m	5	3 Working Days	10
FR60/CR100	Thermo-Loc FR60 Cavity Closer CR 100mm Cav x 2.4m	5	3 Working Days	10
FR60/CR125	Thermo-Loc FR60 Cavity Closer CR 125mm Cav x 2.4m	5	3 Working Days	10
FR60/CR150	Thermo-Loc FR60 Cavity Closer CR 150mm Cav x 2.4m	5	3 Working Days	10
CCFIX	Thermo-loc Cavity Closer Fixing Ties Pack of 100	100	Next Working Day	10
FR60/175	Thermo-Loc FR60 + Cavity Closer 175mm Cav x 2.4m	2	Variable (See P.11)	11
FR60/200	Thermo-Loc FR60 + Cavity Closer 200mm Cav x 2.4m	2	Variable (See P.11)	11
FR60/225	Thermo-Loc FR60 + Cavity Closer 225mm Cav x 2.4m	2	Variable (See P.11)	11
FR60/250	Thermo-Loc FR60 + Cavity Closer 250mm Cav x 2.4m	2	Variable (See P.11)	11
FR60/275	Thermo-Loc FR60 + Cavity Closer 275mm Cav x 2.4m	2	Variable (See P.11)	11
FR60/300	Thermo-Loc FR60 + Cavity Closer 300mm Cav x 2.4m	2	Variable (See P.11)	11
3322	Thermo-Loc FR60 + Fixing Flange - 4 Pack	4	Next Working Day	11
FRSTOP50	FRstop Fire Rated Cavity Stop Sock Masonry 50mm Cav x 1.2m	1	Next Working Day	12
FRSTOP75	FRstop Fire Rated Cavity Stop Sock Masonry 75mm Cav x 1.2m	1	Next Working Day	12
FRSTOP85	FRstop Fire Rated Cavity Stop Sock Masonry 85mm Cav x 1.2m	1	Next Working Day	12
FRSTOP90	FRstop Fire Rated Cavity Stop Sock Masonry 90mm Cav x 1.2m	1	Next Working Day	12
FRSTOP100	FRstop Fire Rated Cavity Stop Sock Masonry 100mm Cav x 1.2m	1	Next Working Day	12
FRSTOP115	FRstop Fire Rated Cavity Stop Sock Masonry 115mm Cav x 1.2m	1	Next Working Day	12
FRSTOP125	FRstop Fire Rated Cavity Stop Sock Masonry 125mm Cav x 1.2m	1	Next Working Day	12
FRSTOP150	FRstop Fire Rated Cavity Stop Sock Masonry 150mm Cav x 1.2m	1	Next Working Day	12

TSSERMO-LOC  
**CAVITY CLOSERS**  
& STOP SOCKS

**timloc**  
building products



**Sales** | Phone: **01405 765 567** Email: [sales@timloc.co.uk](mailto:sales@timloc.co.uk) Web: [www.timloc.co.uk](http://www.timloc.co.uk)

**Technical** | Phone: **01405 782 769** Email: [technical@timloc.co.uk](mailto:technical@timloc.co.uk) Web: [www.timloc.co.uk](http://www.timloc.co.uk)

**Timloc Building Products** | Timloc House, Ozone Park, Howden, East Yorkshire DN14 7SD  
Cavity Closers & Stop Socks | 2024 Edition 1