

TELESCOPIC UNDERFLOOR VENT
EXTENSION ACCESSORIES

INSTALLATION ADVICE

Accessories for various underfloor ventilation
applications for 1201 / 1201XL / 1201XL+



1204

-  Manufactured to BS EN ISO 9001 and BS EN ISO 14001
-  Satisfies all NHBC requirements
-  Complies with all relevant Building Regulations
-  Meets all relevant British Standards

- 1.** **1203** should be fitted with the slotted end to accept the airbrick. 1203 sleeves can also be slotted together to form longer sections if required.
- 2.** **1204** fits externally over the upper and lower parts of the ventilator, units can be multi stacked for greater height.
- 3.** **1205** has a 'push-fit' opening for the drainage pipe. The vermin grille of the ventilator can be left in position. For fitting to drainage pipe a coupling will be required.
- 4.** **1206** fits over the lower rear opening of the ventilator. The vermin grille must be removed to allow this & replaced at the other end of the extension sleeve. 1206s can be slotted together to form longer sections.
- 5.** To improve joins between the telescopic underfloor ventilator and an accessory, seal using insulating tape or duct tape.
- 6.** When incorporating with a gas barrier system and adjusted to the required height, the joining sections should be sealed with proprietary tape.



Scan or click to view the
product datasheet